

Product Overview

Description

The iMCM is an Internet-connected information management system. It provides complete control over weighing, rating, processing and accounting of all outbound mail and shipping.

iMCM allows users to choose any domestic and international carriers — such as FedEx, UPS, DHL and USPS — compare rates on-line, and in some instances (FedEx) permits users to process shipping directly via the carrier's website. iMCM also gives users the ability to add any local or custom carriers.

The iMCM system produces multi-carrier-compliant, two-dimensional barcoded labels that include a user's tracking number, routing detail and address information for fast, accurate and economical control.

With its Internet capability, iMCM allows users to track shipments on-line. And, with some carriers, it will notify users when a delivery will be made.

Designed specifically for Windows® operating systems, iMCM provides a dedicated screen containing complete information and prompts for optimum productivity. A knowledge of the Windows operating system is not necessary to work with iMCM.

Features

- Internet connectivity
- Real Time Interface capability provides access to send/receive data to/from an ODBC compliant database
- Differential weighing for letters, parcels and flats
- Optional module that will process and print all forms needed for USPS eCertified and Certified mail, including the USPS Firm Mailer Book (Form 3877)
- Easy access to printable management reports
- Generates carrier-approved, barcoded labels with tracking information, ship to and return addresses, routing and tracking information
- Accounting information is available in many compatible formats, including Microsoft Access®, Excel, Word, Lotus Notes and many additional formats
- Limits duplicate package ID checking to the open manifest only
- Provides email notification for shipped, delivered or both
- UPS ONLINE®-COMPLIANT
- Process and monitor USPS Delivery and Signature Confirmation Services, including tracking and proof of delivery
- FedEx Air on-line-compliant to process FedEx Domestic air letters and packages

Product Overview

- MAC Certified for manifesting USPS domestic First Class, Priority Mail, Media, Library and Bound Printed Matter mail, as well as International Letter Post and International Parcel Post. Access all USPS special services except Registered Mail
- Seamless interface to all Hasler postage meters, including WhisperJet™ and PowerPost with Dynamic Weighing capability
- Multi user (network) configuration available

System Requirements

PC Specifications – All Configurations

Specifications

Processor	Intel Pentium 4 Processor 2.4 GHz
Memory	256 MB RAM Standard
Storage	Hard Disk Drive – 40 GB Floppy Disk Drive CDRW – re-writeable CD-ROM Drive
Input Devices	Wireless Keyboard with built-in trackball Optional touch screen monitors, 12 & 15 inch available P/S 2 input connections available for conventional keyboard & mouse
Communications	Internal 56 K Modem Built in 10/100 mbps LAN interface Built in 1000 mbps LAN Port (616A port)
Port Configuration	3 Serial Ports – COM1, COM2, COM3 1 Parallel Port – LPT1 4 USB 2.0 Ports – 4 ports total (2 front panel, 2 rear panel) Sound – Speaker connection, Microphone connection (front and rear) 2 SPDIF ports – 1 front, 1 rear (Sony/Phillips Digital Interface)
Dimensions	Height = 7.30 inches Width = 7.88 inches Length = 11.82 inches
Operating System	All configurations – Windows XP Professional

System Requirements

Monitor Specifications – Flat Panel Monitors All Configurations

Specifications

FS15 15 inch Flat Screen monitor

15" TFT Active Matrix LCD panel
Anti Glare "hard" coated surface

Display Size	12.0" x 9.0" (304.1 mm x 228.1 mm)
Pixel Pitch	.297 x.297 (.30)
Resolution	XGA 1024 x 768
Colors	16 Million +
Audio	2 – 1 Watt Built in Speaker
Dimensions	15.4" H x 16.1" W x 7.7" D
Weight	11.9 lbs. (5.4 kg)

FS17 17 inch Flat Screen monitor

17" TFT Active Matrix LCD panel
Anti Glare "hard" coated surface

Display Size	13.3" x 10.6" (337.92 mm x 270.34 mm)
Pixel Pitch	.264
Resolution	XGA 1280 x 1024
Colors	16 Million +
Audio	2 – 2 Watt Built in Speaker
Dimensions	16.5" H x 16.4" W x 6.5" D
Weight	12 lbs. (14.4 kg)

System Requirements

Monitor Specifications – Touch Screen Monitors All Configurations

Specifications

MCMTS12 12.5 inch Touch Screen monitor	12.5" TFT Active Matrix LCD panel "Accutouch" touch Panel, anti glare coating
Display Size	12" Diag. (246 x 185 mm)
Pixel Pitch	.27
Resolution	XGA 800 x 600
Colors	16 Million +
Audio	2 – 1 Watt Built in Speaker
Dimensions	14.0" H x 14.4" W x 6.5" D
Weight	10 lbs. (8.5 kg)
MCMTS15 15 inch Touch Screen monitor	15" TFT Active Matrix LCD panel
Display Size	15" Diag. (38.1 cm diag.)
Pixel Pitch	.297 (.30)
Resolution	XGA 1024 x 768
Colors	16 Million +
Audio	2 – 1 Watt Built in Speaker
Dimensions	372 mm H x 171 mm W x 355 mm D
Weight	9 lbs. (3.7 kg)